



The Exit Terminal PKM stands out as a smart solution, as it combines high-performance technology with strict budgets.

Installation details

Operating temperature:	From -20°C to +55°C with heating, from -0°C to +55°C without heating.
Power supply:	100-120 / 220-240 VAC 50-60 Hz.
Maximum consumption:	100 W (250 W with heater).
Sizes:	1100 mm x 270 mm x 330 mm (height x width x depth).

Standard composition

Front

- Graphic display 240x64 pixel.
- Intercom button.

Components

- Embedded PC based on x86 architecture and SSD storage.
- QR bar code reader.

External and safety finish

- AISI 430 stainless steel polyester powder-painted with oven-dried casing, suitable for outdoor use.
- Single side hatch.
- Height x Width x Depth (mm): 1100 x 270 x 330.

Communications

- Ethernet Communications Connection (TCP/IP).
- Barrier controlled by GPIO.

Certification

Directive 2004/108/EC, Directive 2006/95/CE, UNE-EN 61000-6-3, UNE-EN 61000-6-1, EN 301 489-1 V1.9.2, EN 301 489-3 V1.6.1, UNE-EN 60950-1.

Functions

- Self-adjusting electronic vehicle presence detector.

Degree of protection

- UNE-EN 20324 (EN 60529). Degree of protection of the external structure: IP54.

Options

Components

- RFID proximity card reader for the control of the subscribers.
- Electronically regulated interior heating and ventilation system.
- IP Intercom for communication with the control centre (optional).
- Pinhole camera for capturing facial images (optional).

